

MODEL No.

LIC-558U

Accepts Bundy W type dies and Kearney/
Blackburn O type dies



LIC-558U shown with BP-14LN

SPECIFICATIONS

Ram stroke : 13 mm
Motor : 14.4 VDC

Reservoir capacity : 100 cc
Force at die face : 54 kN

BP-14LN Battery use only.

SIZE

332 (L) x 295 (H) x 84 (W) mm

WEIGHT

3.4 kg (less battery)

ACCESSORIES

Double molded carrying case,
Shoulder Strap
Battery and charger

REMARKS

Dies are sold separately.
Specify the manufacturer's die and
connector numbers.
Specify charger input voltage.

- * Battery operated compression tool
- * Detachable latch type H framed tool head
- * 25CAT cutter attachment as an optional accessory
- * LED lights when battery capacity becomes low
- * Light weight and slim design
- * Pistol type, well balanced design
- * Right or Left handed operation
- * Accepts both Bundy and Kearney type dies (W and O type dies)
- * D3 Saddle dies
- * 180 degree swivel head
- * Optional DC charger
- * Quality backed by ISO9001

FEATURES

The LIC-558U is a compression tool operated by eco-friendly Li-Ion battery.
This tool accepts Bundy W type dies and kearney / Block burn O type dies.

Electronic circuit board with LED indicates compression status and battery capacity.
The LIC-558U has electronic memory function to record repair history by connecting optional "ROBO-RW" analyzer.

It squeezes commonly used service entrance connectors, lugs, sleeves, H and C taps. It can be easily carried and used in limited access areas because of its swivel head and compact design.

Attached quick release pins make changing between compression head and cutting head a one minute job, with no pins or springs to lose! This revolutionary design eliminates the need for multiple tools at one job site.

The 25CAT cutter attachment can slice nonferrous cables up to 25mm.

