



### YC & 2YC-Type Stud Clamp For Stud To Twin Stranded Conductor

Type No.	Catalogue No.	Stud (S)	Cond. (T)	T/O Angle	Max. Rating Amps	A	B	C	D	A/F mm	Unit Weight
YC-1	C20553	38	2X26.5	0°	1600	290	130	88	150	36	3.80kg
YC-2	C20563	38	2X38.3	0°	2500	290	130	88	150	49	4.20kg
YC-3	C20573	38	2X26.5	45°	1600	287	130	88	150	36	3.80kg
YC-4	C20583	38	2X38.3	45°	2500	287	130	88	150	49	4.20kg
YC-5	C20593	38	2X26.5	90°	1600	135	130	88	150	36	3.80kg
YC-6	C20603	38	2X38.3	90°	2500	135	130	88	150	49	4.20kg
YC-7	C20613	60	2X38.3	0°	2500	340	185	146	150	49	6.50kg
YC-8	C20623	60	2X38.3	45°	2500	337	185	146	150	49	6.50kg
YC-9	C20633	60	2X38.3	90°	2500	185	185	146	150	49	6.50kg
YC-10	C20643	26	2X26.5	0°	1600	270	130	82	150	36	3.20kg
YC-11	C20653	26	2X26.5	45°	1600	267	130	82	150	36	3.20kg
YC-12	C20663	26	2X26.5	90°	1600	130	130	82	150	36	3.20kg
YC-25	C20813	60	2X26.5	90°	1600	185	185	146	150	36	6.20kg
YC-26	C20823	60	2X26.5	45°	1600	337	185	146	150	36	6.20kg
YC-27	C20833	60	2X26.5	0°	1600	340	185	146	150	36	6.20kg
2YC-10	C20943	26	2X26.5	0°	1600	270	130	82	330	36	4.60kg
2YC-11	C20953	26	2X26.5	45°	1600	267	130	82	330	36	4.60kg
2YC-12	C20963	26	2X26.5	90°	1600	130	130	82	330	36	4.60kg
2YC-13	C20973	38	2X38.3	0°	2500	290	130	88	330	49	5.60kg
2YC-14	C20983	38	2X38.3	45°	2500	287	130	88	330	49	5.60kg
2YC-15	C20993	38	2X38.3	0°	2500	135	130	88	330	49	5.60kg
2YC-1	C20853	60	2X38.3	0°	2500	330	150	107	330	49	8.00kg
2YC-3	C20873	60	2X38.3	45°	2500	330	150	146	330	49	8.00kg
2YC-5	C20893	60	2X38.3	90°	2500	330	150	146	330	49	8.00kg

- Note:**
- 1) Stud contact surface areas are smooth bore.
  - 2) Other conductor and stud sizes are available on request.
  - 3) Compression tubes are marked showing crimp positions and die sizes.
  - 4) Material: Cast Aluminium  
: Bolts & Nuts-Steel H.T.8.8 H.D.G.
  - 5) Voltage: 500kV Max.