



YC & 2YC-Type Palm Clamp For Twin Conductor Palm Tap-off

Type No.	Catalogue No.	Palm IEC 518	Cond. $\text{\textcircled{T}}$	T/O Angle	Max. Rating Amps	A	D	Palm Size		A/F mm	Unit Weight
								X	Y		
YC-13	C20673	9 BOLT	2X38.3	0°	2500	300	150	125	125	49	2.70kg
YC-14	C20683	9 BOLT	2X38.3	45°	2500	284	150	125	125	49	2.70kg
YC-15	C20693	9 BOLT	2X38.3	90°	2500	185	150	125	125	49	2.70kg
YC-16	C20703	8 BOLT	2X38.3	0°	2500	275	150	200	100	49	3.00kg
YC-17	C20713	8 BOLT	2X38.3	45°	2500	252	150	200	100	49	3.00kg
YC-18	C20723	8 BOLT	2X38.3	90°	2500	135	150	200	100	49	3.00kg
YC-19	C20733	9 BOLT	2X26.5	0°	1600	300	150	125	125	36	2.30kg
YC-20	C20743	9 BOLT	2X26.5	45°	1600	277	150	125	125	36	2.30kg
YC-21	C20753	9 BOLT	2X26.5	90°	1600	160	150	125	125	36	2.30kg
YC-22	C20763	8 BOLT	2X26.5	0°	1600	275	150	200	100	36	2.60kg
YC-23	C20773	8 BOLT	2X26.5	45°	1600	252	150	200	100	36	2.60kg
YC-24	C20783	8 BOLT	2X26.5	90°	1600	135	150	200	100	36	2.60kg
2YC-2	C20863	9 BOLT	2X38.3	0°	2500	300	330	125	125	49	3.30kg
2YC-4	C20883	9 BOLT	2X38.3	45°	2500	284	330	125	125	49	3.30kg
2YC-6	C20903	9 BOLT	2X38.3	90°	2500	185	330	125	125	49	3.30kg
2YC-7	C20913	8 BOLT	2X38.3	0°	2500	275	330	200	100	49	3.60kg
2YC-8	C20923	8 BOLT	2X38.3	45°	2500	252	330	200	100	49	3.60kg
2YC-9	C20933	8 BOLT	2X38.3	90°	2500	135	330	200	100	49	3.60kg

- Note:**
- 1) Palm contact surface areas are serrated.
 - 2) Palms are drilled to either IEC 518 : 9 Dia. 14 Holes at 40mm centres.
or : 8 Dia. 14 Holes at 50mm centres.
 - 3) Other conductor sizes are available on request.
 - 4) Compression tubes are marked showing crimp position and die sizes.
 - 5) Material: Cast Aluminium
 - 6) Voltage : 500kV Max.