


IEC 8 Hole Pad



IEC 9 Hole Pad

### 3YC-Type Palm Clamp For Triple Conductor Palm Tap-off

Type No.	Catalogue No.	Palm IEC 518	Cond. $\text{\textcircled{T}}$	T/O Angle	Max. Rating Amps	A	D	Palm Size		A/F mm	Unit Weight
								X	Y		
3YC-2	C21063	9 BOLT	3X38.3	0°	3500	300	165	125	125	49	4.20kg
3YC-4	C21083	9 BOLT	3X38.3	45°	3500	300	165	125	125	49	4.20kg
3YC-6	C21103	9 BOLT	3X38.3	90°	3500	300	165	125	125	49	4.20kg
3YC-7	C21113	8 BOLT	3X38.3	0°	3500	275	165	200	100	49	4.50kg
3YC-8	C21123	8 BOLT	3X38.3	45°	3500	275	165	200	100	49	4.50kg
3YC-9	C21133	8 BOLT	3X38.3	90°	3500	275	165	200	100	49	4.50kg

- Note:**
- 1) Palm contact surface areas are serrated.
  - 2) Palms are drilled to either IEC 518 : 9 Dia. 14 Holes at 40mm centres.  
or : 8 Dia. 14 Holes at 50mm centres.
  - 3) Compression tubes are marked showing crimp position and die sizes.
  - 4) Material: Cast Aluminium
  - 5) Voltage : 500kV Max.