



YP-Type Palm Clamp For Twin Conductor Palm Tap-off

Type No.	Catalogue No.	Conductor ®	Centre Spacing D	Max. Rating Amps	Palm Size		A	B	Unit Weight
					X	Y			
YP-1	C21833	2X26.5	150	1600	125	125	242	95	4.90kg
YP-2	C21843	2X38.3	150	2500	125	125	247	105	5.20kg
1YP-1	C21883	2X38.3	200	2500	125	125	305	105	5.40kg
1YP-2	C21893	2X38.3	200	2500	125	160	343	105	6.10kg
1YP-3	C21873	2X38.3	200	2500	200	100	285	105	6.70kg
2YP-3	C21853	2X26.3	330	1600	125	125	245	95	5.30kg
2YP-4	C21863	2X38.3	330	2500	125	125	245	105	5.90kg

- Note:**
- 1) Conductor and Palm contact surface areas are serrated.
 - 2) Palms are drilled to either IEC 518 : 9 Dia. 14 Holes at 40mm centres. Standard.
or : 8 Dia. 14 Holes at 50mm centres. On Request.
 - 3) Palms may also be supplied undrilled or to suit requirements.
 - 4) Other palm sizes, centre spacings and conductor sizes are available on request.
 - 5) Material: Cast Aluminium
 - 6) Voltage: 500kV Max.

Note:

**McWade
Productions (Pty) LTD**

P.O.BOX 142 Olifantsfontein, 1665-Gauteng, South Africa
TEL(+27)11-316-2262 FAX(+27)11-316-4791
www.mcwade.co.za

Ver.1 04/03

Protected By Copyright