



K-Type Cross Clamp For Stud to Stranded Conductor

Type No.	Catalogue No.	Cond. Ⓡ	Stud Ⓣ	Max. Rating Amps	A	B	C	Unit Weight
K-1	C20013	16.3	26.0	500	173	95	70	1.83kg
K-2	C20023	26.5	26.0	900	198	95	95	2.66kg
K-3	C20033	16.3	38.0	500	188	105	70	2.16kg
K-4	C20043	26.5	38.0	900	209	105	95	2.90kg
K-5	C20053	38.3	38.0	1350	218	105	105	3.00kg
K-6	C20063	19.0	38.0	600	182	105	70	1.99kg
K-7	C20073	26.5	35.0	900	209	105	95	2.16kg
K-8	C20083	38.3	35.0	950	218	105	105	2.90kg
K-9	C20093	19.0	26.0	600	173	95	70	1.83kg
K-10	C20103	21.0	26.0	650	198	95	95	1.99kg

- Note:**
- 1) Conductor contact surface areas are serrated.
 - 2) Stud contact surface areas are smooth bore.
 - 3) Other conductor and stud sizes are available on request.
When ordering, Run and Tap are to be specified stating diameter and whether conductor/conductor or conductor/stud; and sizes required.
 - 4) Material: Cast Aluminium
: Bolts & Nuts—Steel HT.8.8. H.D.G.
 - 5) Voltage: 500kV Max.