



TC-Type Tee Clamp For Stranded Conductor

Type No.	Catalogue No.	Cond. Size		Max. Rating Amps	A	B	C	No Of Caps	A/F	Unit Weight
		Ⓜ	Ⓣ							
TC-1	C20153	23.5	26.5	650	255	124	70	3	36	1.90kg
TC-2	C20163	23.5	38.3	650	250	124	70	3	49	2.30kg
TC-3	C20173	26.5	26.5	900	255	124	70	3	36	1.90kg
TC-4	C20183	26.5	38.3	900	240	124	70	3	49	2.30kg
TC-5	C20193	28.6	26.5	900	255	124	70	3	36	1.90kg
TC-6	C20203	28.6	38.3	900	240	124	70	3	49	2.30kg
TC-7	C20213	35.6	26.5	900	270	175	88	3	36	2.90kg
TC-8	C20223	35.6	38.3	1100	270	175	88	3	49	3.00kg
TC-9	C20233	38.3	26.5	900	270	175	88	3	36	3.50kg
TC-10	C20243	38.3	38.3	1350	270	215	88	4	49	3.60kg
TC-11	C20253	18.1	26.5	450	255	124	70	3	36	1.70kg
TC-12	C20263	18.1	18.1	450	261	124	70	3	30	1.70kg
TC-13	C20273	26.5	18.1	450	261	124	70	3	30	1.70kg
TC-14	C20283	38.3	18.1	450	255	124	70	3	36	1.70kg
TC-15	C20293	38.3	16.0	450	261	124	70	3	30	1.70kg
TC-16	C20533	26.5	16.0	450	261	124	70	3	30	1.70kg
TC-17	C20543	16.0	16.0	450	261	124	70	3	30	1.70kg

- Note:**
- 1) Conductor contact surface areas are serrated.
 - 2) Compression tubes are marked showing crimp positions and die sizes.
 - 3) Other conductor sizes are available on request.
 - 4) Material: Cast Aluminium
: Bolts & Nuts-Steel HT.8.8 H.D.G.
 - 5) Voltage : 500kV Max.