



SPC-Type Palm Clamp For Stranded Conductor

Type No.	Catalogue No.	A	Palm Size		Hole Centres	Cond. $\text{\textcircled{T}}$	Max. Rating Amps	T/O Angle	A/F	Unit Weight
			X	Y						
SPC-1	C21203	285	80	90	50X50	26.5	900	0°	36	1.00kg
SPC-2	C21213	N/A	80	90	50X50	26.5	900	45°	36	1.00kg
SPC-3	C21223	N/A	80	90	50X50	26.5	900	90°	36	1.00kg
SPC-4	C21233	280	80	90	50X50	38.3	1350	0°	49	1.20kg
SPC-5	C21243	N/A	80	90	50X50	38.3	1350	45°	49	1.20kg
SPC-6	C21253	N/A	80	90	50X50	38.3	1350	90°	49	1.20kg
SPC-7	C21263	325	125	125	80X80	26.5	900	0°	36	1.40kg
SPC-8	C21273	N/A	125	125	80X80	26.5	900	45°	36	1.40kg
SPC-9	C21283	N/A	125	125	80X80	26.5	900	90°	36	1.40kg
SPC-10	C21293	320	125	125	80X80	38.3	1350	0°	49	1.60kg
SPC-11	C21303	N/A	125	125	80X80	38.3	1350	45°	49	1.60kg
SPC-12	C21313	N/A	125	125	80X80	38.3	1350	90°	49	1.60kg
SPC-13	C21323	285	80	90	BLANK	26.5	900	0°	36	1.00kg
SPC-14	C21333	320	125	125	BLANK	38.3	1350	0°	49	1.20kg

- Note:**
- 1) Palm contact surface areas are serrated.
 - 2) Palms are supplied drilled with 4-Dia.14 Holes to specified centres.
 - 3) Palms may be drilled to suit other hole centres specified.
 - 4) Compression tubes are marked showing crimp positions and die sizes.
 - 5) Other conductor sizes are available on request.
 - 6) Material: Cast Aluminium
: Bolts & Nuts- Steel HT.8.8 H.D.G.
 - 7) Voltage: 300kV Max.