



Compression Dead Ends For ACSR Conductors

Conductor		Catalogue No.	A	B	A/F		Alcan Die		UTS Cond. kN	Unit Weight
Name	Dia.				Alu.	Stl.	Alu.	Stl.		
Fox	8.38	L4011013	415	2XM12	13.5	6.0	BIMETAL 4E		13.24	1.05kg
Mink	10.98	L4011023	415	2XM12	17.0	7.2	DA5		22.07	1.15kg
Horse	13.95	L4011293	465	2XM12	25.4	12.7	DA7	DS8	59.85	1.83kg
Dog	14.17	L4011303	465	2XM12	25.4	10.1	DA7	DS7	32.48	1.88kg
Hare	14.21	L4011033	465	2XM12	25.4	10.1	DA7	DS7	37.42	1.30kg
Leopard	15.81	L4011133	465	2XM12	25.4	12.7	DA7	DS8	40.65	1.92kg
Tiger	16.53	L4011173	465	2XM12	25.4	12.7	DA7	DS8	56.52	1.30kg
Wolf	18.13	L4011043	470	2XM12	28.2	12.7	DA8	DS8	67.50	1.30kg
Chickadee	18.87	L4011053	470	2XM12	28.2	12.7	DA8	DS8	44.68	1.99kg
Lynx	19.56	L4011143	470	2XM12	28.2	12.7	DA8	DS8	78.00	2.00kg
Pelican	20.67	L4011333	515	2XM12	28.2	12.7	DA8	DS8	52.83	2.10kg
Panther	21.00	L4011063	515	2XM12	32.3	15.2	DA9	DS9	89.92	2.10kg
Bear	23.47	L4011073	555	2XM12	32.3	16.1	DA9	DS10	111.13	2.00kg
Kingbird	23.87	L4011083	555	2XM12	32.3	12.7	DA9	DS8	69.80	2.00kg
Goat	25.96	L4011093	570	3XM12	36.2	16.1	DA10	DS10	135.0	2.20kg
Bison	26.97	L4011183	570	3XM12	36.2	16.1	DA10	DS10	116.60	2.20kg
Tern	27.00	L4011323	570	3XM12	40.2	12.7	DA11	DS8	101.91	2.35kg
Zebra	28.56	L4011103	570	3XM12	40.2	16.1	DA11	DS10	130.49	2.45kg
Bersford	35.56	L4011123	565	4XM12	49.7	16.1	DA13	DS10	177.64	3.25kg
Dinosaur	35.94	L4011113	565	4XM12	49.7	20.2	DA13	DS12	180.64	3.25kg

- Note:** 1) Compression tubes are marked showing conductor name, crimp positions and die size.
 2) Other conductor sizes are available on request.
 3) Material: Extruded Aluminium.
 : Eye Bolt—D.F.Steel H.D.G.
 : Bolts & Nuts—Steel H.D.G.