

MODEL No.

# REC-54

Maximum cutting diameter : Nonferrous 54 mm and  
Steel supported 400 pair telecom cable



REC-54 shown with BP-70I



REC-54 shown with SS cable



## SPECIFICATIONS

Drive unit : 14.4V DC Motor

## SIZE

105 (L) x 410 (H) x 115 (W) mm

## WEIGHT

2.5 kg (less battery)

## ACCESSORIES

Steel carrying case,  
Battery and charger  
(See selection Battery &  
Compatibility Chart)

## FEATURES

The REC-54 was designed to cut SS cable or overhead CCP cable with Steel strand Support.

It cuts both nonferrous cables and steel strands. Like the REC-50, cuts are clean with minimal cable distortion.

A circuit breaker for overloading protection prevents motor overheating when attempting to cut the material over its capacity.

## REMARKS

Cutting capacity : # of cuts

Material	BP-70MH
Polyethylene cable	
600V-CV325 mm <sup>2</sup> (31 mm OD)	: 90
Multi-core vinyl insulation cable	
VVR150 mm <sup>2</sup> (47 mm OD) 3 core	: 45
SB-ACSR120 mm <sup>2</sup> (18.6 mm OD)	: 142
Hard aluminum cable	
HAL-OC400 mm <sup>2</sup> (31.9 mm OD)	: 120
Hard copper cable	
OE-OC150 mm <sup>2</sup> (21 mm OD)	: 165
SS cable	
0.4 mm 400 CCP-F-SS(CR) cable	: 142
LCCP cable without support wire	
54 mm outer diameter	: 187