

MODEL No.

REC-55PDF

Punching capacity : 3.2 mm thick mild steel or 1.6 mm stainless steel with 104 mm (4") holes



REC-55PDF shown with BP-70EI



Example of punch set

**SPECIFICATIONS**

Ram stroke : 22 mm
Motor : 14.4 VDC

Reservoir capacity :
100 cc
Output force :
73 kN

SIZE

328 (L) x 254 (H) x 70 (W) mm

WEIGHT

3.8 kg (less battery)

ACCESSORIES

Standard Accessories:

Shoulder strap,
Double molded carrying case,
Setting threads (3/4 and 3/8),
Punches are sold separately,
Collar (L, M, S, SS)
Battery and charger,
(See selection Battery &
Compatibility Chart)

※ Punch set is sold separately.

REMARKS

Specify charger input voltage.

Ordering information :

REC-55PDF	standard accessories only
REC-55PDF(A)	above plus A19 to A51 punch set
REC-55PDF(B)	above plus B16 to B54 punch set

Detail information of punch is shown on page of SH-10 (Page 100)

FEATURES

The REC-55PDF is a battery operated punch driver with swivel head for easy access to tight enclosed control panels. It gives clean perforation through 3.2mm thick mild steel or 1.6mm stainless steel with 104mm (4") holes.

This tool is ideal for working on control panels.

See SH-10(A)P and SH-10(B)P page 92 for punch sizes.

The number of perforations per charge for 3" hole on 3.2mm steel :
52 perforations / BP-70MH