

MODEL No.

**AC-5ND**Insulated terminals : 2.0 mm<sup>2</sup> (blue)

### SPECIFICATIONS

Applicable air pressure :  
0.48–0.58 Mpa  
Air consumption : 34 liters/min at  
30 crimps/min  
Output force :  
12.7 kN at 0.48 Mp air pressure

### SIZE

215 (L) x 135 (H) x 90 (W) mm

### WEIGHT

2.7 kg with Foot pedal

### ACCESSORIES

Standard foot pedal  
Jaws are sold separately



AC-5ND



Example of AC-5ND Jaws

### FEATURES

- \* Capable of crimping several types of terminals up to 5.5mm<sup>2</sup> with interchangeable jaws.
- \* Bench mounted, air operated AC-5ND is suitable for continuous crimping for production line.

AF2 foot pedal adjusts jaw butting time by air timer so that butting time is regulated regardless of operator. This will prevent spring back of crimped terminal and maintain constant crimp heights.

### REMARKS

Optional Jaw

Jaw #	Applicable terminals
# 1 Jaw	Non-insulated 1.25, 2, 5.5 mm <sup>2</sup>
# 3 Jaw	Insulated 1.25 mm <sup>2</sup>
# 4 Jaw	Insulated 2 mm <sup>2</sup>
# 5 Jaw	Insulated 5.5 mm <sup>2</sup>
# 7A Jaw	Closed End 1.3-3, 2-6 mm <sup>2</sup>
F-200 Jaw	Tab 0.5-1.25, 2 mm <sup>2</sup>
Cutter Jaw	Cu, Al wire 7 mm O.D.