

MODEL No.  
**LP-430B**

Accepts existing **12 ton** U-type dies



LP-430B

**SPECIFICATIONS**

Jaw Opening : 30mm

Force at die face :  
110 kN

**SIZE**

127 (Dia) x 557 (L) mm

**WEIGHT**

8.4 kg



Example of dies

**FEATURES**

The LP-430B hydraulic tool is directly powered by PTO (Power Take Off) from utility bucket trucks or any vehicle with a low pressure hydraulic circuit having Line pressure of 13.7Mpa or 2,000 PSI and a maximum flow of 35 liters/min. or 9 GPM.

The LP-430B is designed to operate with either Open-Center or Closed Center hydraulic system by rotating the head to the position.

The LP-430B has the same compression head as the EP-431 so that dies are interchangeable with all 12 ton U-type dies.

It has built-in relief valve to prevent overloading the tool from more than 13.7Mpa or 2,000 PSI of input pressure.

LP-430B is fitted with a two step safety trigger to assist in eliminating accidental operation.

Trigger guard is rubber coated to protect user against sharp edges.

**REMARKS**

- \* Low pressure hydraulic compression tool
- \* Direct power input from truck PTO
- \* Relief setting at 13.7Mpa (2,000 PSI)
- \* Suitable for bucket truck use
- \* Specify the manufacturer's die and connector numbers