

MODEL No.

P-132

Cuts insulated cables up to 132 mm



P-132



P-132 shown with P-60


SPECIFICATIONS

Maximum input pressure : 68.5Mpa (10.000 PSI)

Oil volume required : 220 cc

Output force : 95 kN

SIZE

630 (L) mm

WEIGHT

12.0 kg

ACCESSORIES

Carrying bag

FEATURES

P-132 hydraulic cutter head features :

- * Cuts underground or armored cables (depends on type)
- * Fast cutting with remote operation
- * Guillotine type cutting for less jamming than shear type cutting
- * 132mm jaw opening accepts larger size cables
- * Can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)
- * Equipped with NPT 3/8" threaded Parker type high pressure couplers
- * Blades are easily replaceable
- * Lock pin type cutter head

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Cu strands	: 42 mm
Al strands	: 46 mm

Wire rope 6x7	: N/A
Wire rope 6x12	: N/A
Wire rope 6x19	: N/A
Soft steel bar	: N/A
Reinforcing rod	: N/A
ACSR	: N/A
Guy wire 1x7	: N/A
Guy wire 1x19	: N/A

*Quality backed by ISO 9001