

MODEL No.  
**S-320**

Cuts heavy steel materials up to 32 mm



S-320



S-320 shown with Reinforcing rod

**FEATURES**

Light weight portable hydraulic cutter features :

- \* Two stage pumping for rapid blade advance
- \* Safety relief valve for overload protection
- \* Guillotine type cutting for less jamming than shear type cutting
- \* No set-up time required
- \* Blades are easily replaceable
- \* 180 degree swivel and latch type head allows easy cutting position

**SPECIFICATIONS**

Maximum handle load : 276 N  
 Two stage pumping  
 Relief valve is equipped  
 Reservoir capacity : 202 cc  
 Maximum opening : 35 mm  
 Pumping cycles when no load : 20 times

Output force : 194 kN

**SIZE**

580 (L) mm

**WEIGHT**

12.0 kg

**ACCESSORIES**

Carrying bag

**REMARKS**

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x7	: 32 mm
Wire rope 6 x12	: 32 mm
Wire rope 6 x 19	: 32 mm
Soft steel bar	: 25 mm
Reinforcing rod	: 25 mm
Cu strands	: 32 mm
Al strands	: 32 mm
ACSR	: 32 mm
Guy wire 1 x7	: 32 mm
Guy wire 1 x 19	: 32 mm
CCP cable	: N/A