

MODEL No.

S-400

Cuts steel materials as well as cables up to 41 mm

SPECIFICATIONS

Maximum handle load : 196 N
 Two stage pumping
 Relief valve is not equipped
 Reservoir capacity : 120 cc
 Maximum opening : 42 mm
 Pumping cycles when no load :
 17 times

Output force : 55 kN

SIZE

575 (L) mm

WEIGHT

5.8 kg

ACCESSORIES

Carrying bag



S-400



S-400 (Head opened)

FEATURES

Light weight portable hydraulic cutter features :

- * Two stage pumping for rapid blade advance
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and lock pin type head allows easy cutting position

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x7	: 22 mm
Wire rope 6 x12	: 25 mm
Wire rope 6 x 19	: 25 mm
Soft steel bar	: 20 mm
Reinforcing rod	: 16 mm
Cu strands	: 41 mm
Al strands	: 41 mm
ACSR	: 38 mm
Guy wire 1 x7	: 15 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A