

MODEL No.
S-550

Cuts steel materials as well as cables up to 54 mm



S-550



S-550 (Head opened)

SPECIFICATIONS

Maximum handle load : 276 N
 Two stage pumping
 Relief valve is equipped
 Reservoir capacity : 202 cc
 Maximum opening : 54 mm
 Pumping cycles when no load : 25 times

Output force : 124 kN

SIZE

625 (L) mm

WEIGHT

10.0 kg

ACCESSORIES

Carrying bag

FEATURES

Light weight portable hydraulic cutter features :

- * Two stage pumping for rapid blade advance
- * Safety relief valve for overload protection
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and lock pin type head allows easy cutting position

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x7	: 25 mm
Wire rope 6 x12	: 30 mm
Wire rope 6 x 19	: 30 mm
Soft steel bar	: 22 mm
Reinforcing rod	: 20 mm
Cu strands	: 54 mm
Al strands	: 54 mm
ACSR	: 54 mm
Guy wire 1 x7	: 15 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A