

MODEL No.
SP-24

Cuts steel materials as well as cables
up to 24 mm

SPECIFICATIONS

Maximum input pressure : 68.5 Mpa
Oil volume required : 33 cc

Output force : 86 kN

SIZE

245 (L) mm

WEIGHT

3.1 kg

ACCESSORIES

Carrying bag



SP-24

FEATURES

The SP-24 hydraulic cutter head features :

- * Fast cutting with remote operation
- * It can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)
- * Equipped with PT 3/8" threaded Izumi high pressure couplers
- * PT-NPT adapters are available on request for NPT 3/8" threaded couplers
- * Blades are easily replaceable
- * Flip-top latch for easy insertion of cutting material

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x 7	: 18 mm
Wire rope 6 x 12	: 24 mm
Wire rope 6 x 19	: 24 mm
Soft steel bar	: 20 mm
Reinforcing rod	: 16 mm
Cu strands	: 24 mm
Al strands	: 24 mm
ACSR	: 24 mm
Guy wire 1 x 7	: 20 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A

