

MODEL No.  
**SP-32**

Cuts heavy duty steel materials  
up to 32 mm



SP-32



**FEATURES**

The SP-32 hydraulic cutter head features :

- \* Fast cutting with remote operation
- \* It can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)
- \* Equipped with PT 3/8" threaded izumi high pressure couplers
- \* PT-NPT adapters are available on request for NPT 3/8" threaded couplers
- \* Blades are easily replaceable
- \* Flip-top latch for easy insertion of cutting material

**SPECIFICATIONS**

Maximum input pressure : 68.5 Mpa  
Oil volume required : 135 cc

Output force : 250 kN

**SIZE**

300 (L) mm

**WEIGHT**

10.0 kg

**ACCESSORIES**

Carrying bag

**REMARKS**

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x 7	: 32 mm
Wire rope 6 x 12	: 32 mm
Wire rope 6 x 19	: 32 mm
Soft steel bar	: 25 mm
Reinforcing rod	: 25 mm
Cu strands	: 32 mm
Al strands	: 32 mm
ACSR	: 32 mm
Guy wire 1 x 7	: 32 mm
Guy wire 1 x 19	: 32 mm
CCP cable	: N/A