

MODEL No.

**SP-40A**

Cuts steel materials as well as cables  
up to 41 mm

**SPECIFICATIONS**

Maximum input pressure : 68.5 Mpa  
Oil volume required : 50 cc

Output force : 68 kN

**SIZE**

340 (L) mm

**WEIGHT**

4.0 kg

**ACCESSORIES**

Carrying bag



SP-40A

**FEATURES**

The SP-40A hydraulic cutter head features :

- \* Fast cutting with remote operation
- \* It can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)
- \* Equipped with PT 3/8" threaded izumi high pressure couplers
- \* PT-NPT adapters are available on request for NPT 3/8" threaded couplers
- \* Blades are easily replaceable
- \* Lock pin type cutter head

**REMARKS**

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x 7	: 22 mm
Wire rope 6 x 12	: 25 mm
Wire rope 6 x 19	: 25 mm
Soft steel bar	: 20 mm
Reinforcing rod	: 16 mm
Cu strands	: 41 mm
Al strands	: 41 mm
ACSR	: 38 mm
Guy wire 1 x 7	: 15 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A