

MODEL No.

HPE-2A

Rated pressure : 68.5 Mpa or 10,000 PSI



HPE-2A



HPE-2A shown with EP-605

**SPECIFICATIONS**

Oil delivery :
2.6 liter / min at low pressure
0.5 liter / min at high pressure

Engine : Air cooled
4 cycle gasoline engine
1.5kw (2.0 ps) / 3,600 rpm, leadfree
gasoline
Reservoir capacity : 2.2 liter

SIZE

470 (L) x 330 (W) x 443 (H)mm

WEIGHT

33.5kg (30kg dry)

ACCESSORIES

Remote control switch,
Spark plug wrench

REMARKS

Hydraulic hose sold separately.

- * Remote control operation
- * Pole mounting bracket as a standard accessory
- * Visual oil level
- * External air vent and oil level
- * Compact design
- * Dependable Fuji Heavy's engine
- * For single acting tools

FEATURES

The HPE-2A **single acting** gasoline engine driven hydraulic pump is the most sophisticated engine pump on today's market. It builds pressure to 68.5Mpa automatically and returns engine RPM to an idle.

Wired remote control allows operator complete control. Oil volume is large enough to operate a 60 ton class single acting compression head.

The FUJI HEAVY'S four cycle engine EH09-2D is used with this Pump. This engine meets emission control in accordance with EPA Phase2 and CARB Tier2.

And this engine improves fuel cost by 15% in comparison with former EY08D engine on the HPE-1A.