

MODEL No.

SH-10(A)P
SH-10(B)P

Up to 104 mm diameter hole perforation on 3.2 mm thickness mild steel



SPECIFICATIONS

Punching capacity
Stainless Steel :
1.6 mm plate thickness
Mild steel :
3.2 mm plate thickness
Hole diameter :

up to 104 mm (4 inch) es
Ram Stroke : 25 mm
Oil volume required : 35 cc
Output force : 81 kN at 68.5 Mpa pressure

SIZE

63 (Dia) x 125 (H) mm

WEIGHT

1.9 kg

ACCESSORIES

Milli size punch sets are available on request.
M15, 16, 25, 30, 35, 40, 45, 50, 55, 57, 67, 70, 80, 82, 87, 95, 100, 108, 110

SH-10 (B) P



SH-10(A)P shown with carrying case

FEATURES

Selection Chart :

SH-10 (A) P SH-10 (B) P

- 1 HP-180N Hand Pump
- 2 Setting threads (3/8" & 3/4")
- 3 Collar (Large, Medium, Small)
- 4 Steel carrying case

A19 (3/4")	B16 (1 1/2")
A25 (1")	B22 (3/4")
A31 (1 1/4")	B28 (1")
A39 (1 1/2")	B36 (1 1/4")
A51 (2")	B42 (1 1/2")
	B54(2")

REMARKS

Punching size

Punch	Hole size
A15*	17.6 mm
A19 (3 / 4)	19.8 mm
A25 (1)	26.1 mm
A31 (1 1/ 4)	32.5 mm
A39 (1 1/ 2)	38.7 mm
A51 (2)	51.6 mm
A63 (2 1/ 2)*	64.4 mm
A75 (3)*	77.2 mm
B16 (1/ 2)	21.8 mm
B22 (3/ 4)	27.6 mm
B28 (1)	34.1 mm
B36 (1 1/ 4)	42.7 mm
B42 (1 1/ 2)	48.7 mm
B54 (2)	60.5 mm
B70 (2 1/ 2)*	76.1 mm
B82 (3)*	88.9 mm
B92 (3 1/ 2)*	102.8 mm
B104 (4)*	115.5 mm

(*) marks show optional punch set available