



Drop Out Fuse

TYPE No.	Catalogue No.	Rated Voltage kV	Rated Current Amps	Creepage Distance (mm)	Nema Bracket Assembly	100A Fuse Carrier	200A Solid Link	Dimensions				Unit Weight
								A	B	C	D	
36MZL	S83303	11kV	100	360	✓	✓	460	150	384	496	8.70kg	
36MZO	S89823		100			✓					8.40kg	
36LZL	S83373		200		✓						✓	9.30kg
36LZO	S89833		200			✓					8.40kg	
36WZL	S83293				✓						7.50kg	
36WZO	S89843										7.50kg	
55MZL	S83353	22kV	100	550	✓	✓	530	190	446	385	9.80kg	
55MZO	S89853		100			✓					9.80kg	
55LZL	S83283		200		✓						✓	8.80kg
55LZO	S89863		200			✓					10.6kg	
55WZL	S83383				✓						9.70kg	
55WZO	S89873										9.50kg	
55CMZL	S83343	100	✓	✓		8.50kg						
55CLZL	S82323	200	✓		✓	8.50kg						
65MZL	S81413	33kV	100	650	✓	✓	616	245	526	420	17.0kg	
65MZO	S84313		100			✓					16.0kg	
65LZL	S84333		200		✓						✓	17.0kg
65LZO	S84343		200			✓					16.0kg	
65WZL	S84353				✓						16.0kg	
65WZO	S84363										16.0kg	

- Note :**
- 1) Material: Insulator—Porcelain
: Contacts—Brass
: Fuse tube—Hornfibre
 - 2) Cut-Outs are also available in Cycloaliphatic for 11 and 22kV only.
 - 3) Nema Bracket type to be specified, eg.wood/steel X-Arm.