



TBFX/9-Type Full 90° Expansion Clamp

Type No	Catalogue No	Tube Dia. (R)	P.C.D.	C	H	Max. Rating Amps.	Unit Weight
TBFX/9-80/127/FS	C24863	80	76/127	410	120	2300	12.2kg
TBFX/9-80/127/SS	C24053	80	76/127	410	120	2300	12.2kg
TBFX/9-100/127/FS	C25803	100	76/127	430	120	2800	14.2kg
TBFX/9-100/127/SS	C25053	100	76/127	430	120	2800	14.2kg
TBFX/9-120/127/FS	C26773	120	76/127	472	150	3300	17.3kg
TBFX/9-120/127/SS	C26783	120	76/127	472	150	3300	17.3kg
TBFX/9-150/127/FS	C23453	150	76/127	510	160	4000	20.5kg
TBFX/9-150/127/SS	C23463	150	76/127	510	160	4000	20.5kg
TBFX/9-150/225/FS	C23473	150	225	510	160	4000	20.5kg
TBFX/9-150/225/SS	C23893	150	225	510	160	4000	20.5kg
TBFX/9-160/127/FS	C23953	160	76/127	510	160	4000	21.5kg
TBFX/9-160/127/SS	C23443	160	76/127	510	160	4000	20.5kg
TBFX/9-160/225/FS	C27443	160	225	510	160	4000	21.5kg
TBFX/9-160/225/SS	C27453	160	225	510	160	4000	21.5kg
TBFX/9-200/127/FS	C240123	200	76/127	540	200	5200	26.3kg
TBFX/9-200/127/SS	C240133	200	76/127	540	200	5200	26.3kg
TBFX/9-200/225/FS	C27463	200	225	540	200	5200	26.3kg
TBFX/9-200/225/SS	C27473	200	225	540	200	5200	26.3kg
TBFX/9-250/225/FS	C240143	250	225	560	250	6300	33.5kg
TBFX/9-250/225/SS	C27983	250	225	560	250	6300	33.5kg

- Note:**
- 1) The busbar contact surface areas are serrated.
 - 2) Clamps are supplied either with: 4 Dia. 14 Holes at 76 P.C.D.
or : 8 Dia. 18 Holes at 127 P.C.D.
or : 8 Dia. 18 Holes at 225 P.C.D.
 - 3) Current rating to be specified when ordering.
 - 4) Clamps may be modified to suit different tube sizes.
 - 5) Material: Cast Aluminium
: Bolts & Nuts are Steel HT.8.8. H.D.G. (Other materials and grades available on request)
 - 6) Voltage: 500kV Max.