



TBBT-Type In Line Bus Conductor Tap-off Clamp

Type No	Catalogue No	Tube Dia. (R)	Cond. Dia. (T)	A	Max. Rating Amps.	Unit Weight
TBBT-150/C1-38	C26893	150	1x38	355	1350	11.6kg
TBBT-150/C2-38	C26093	150	2x38	460	2500	11.7kg
TBBT-150/C3-38	C26973	150	3x38	390	3500	13.7kg
TBBT-160/C1-38	C28713	160	1x38	355	1350	11.4kg
TBBT-160/C2-38	C28723	160	2x38	460	2500	12.5kg
TBBT-160/C3-38	C28743	160	3x38	390	3500	13.6kg
TBBT-200/C1-38	C27813	200	1x38	300	1350	12.6kg
TBBT-200/C2-38	C27823	200	2x38	405	2500	13.7kg
TBBT-200/C3-38	C27853	200	3x38	420	3500	15.8kg
TBBT-250/C1-38	C28373	250	1x38	415	1350	13.4kg
TBBT-250/C2-38	C28233	250	2x38	429	2500	14.8kg
TBBT-250/C3-38	C28203	250	3x38	430	3500	17.3kg

- Note:**
- 1) The busbar contact surface areas are serrated.
 - 2) Clamps are designed for 0° + 90° conductor entry.
 - 3) Other conductor sizes and centres are available on request.
 - 4) Material: Cast Aluminium
: Bolts & Nuts are Steel HT.8.8. H.D.G. (Other materials and grades available on request)
 - 5) Voltage: 500kV Max.