



TBCT-Type Bus Conductor Tap-off Clamp

TYPE No.	PART No.	Tube Dia. (R)	Cond. Dia. (T)	A	D	Max. Rating Amps.	Unit Weight
TBCT-80/C1-26	C240003	80	1x26	300	N/A	900	2.25kg
TBCT-80/C1-38	C240013	80	1x38	324	N/A	1350	2.45kg
TBCT-80/C2-26	C24213	80	2x26	300	190	1600	2.76kg
TBCT-80/C2-38	C24233	80	2x38	324	190	2500	3.16kg
TBCT-100/C1-26	C240023	100	1x26	300	N/A	900	2.45kg
TBCT-100/C1-38	C240033	100	1x38	324	N/A	1350	2.65kg
TBCT-100/C2-26	C25183	100	2x26	300	210	1600	2.85kg
TBCT-100/C2-38	C25193	100	2x38	324	210	2500	3.25kg
TBCT-120/C1-26	C240043	120	1x26	305	N/A	900	2.55kg
TBCT-120/C1-38	C240053	120	1x38	320	N/A	1350	2.75kg
TBCT-120/C2-26	C26173	120	2x26	305	230	1600	2.85kg
TBCT-120/C2-38	C26183	120	2x38	320	230	2500	3.05kg

- Note:**
- 1) The busbar contact surface areas are serrated.
 - 2) Clamps are supplied in 3 different angles, 0°, 45°, 90°. when ordering the angle required is to be specified.
 - 3) Other conductor sizes are available on request.
 - 4) Material: Cast Aluminium
: Bolts & Nuts are Steel HT.8.8. H.D.G. (Other materials and grades available on request)
 - 5) Voltage : 500kV Max.